


VIEWSONIC 4,500 ANSI LUMENS WXGA LASER PROJECTOR WITH H/V KEYSTORE, 4 CORNER ADJUSTMENT, 360 DEGREE PROJECTION | LS630W

Key Features


- High Brightness Laser Projector: WXGA (1280x800p) resolution with a 1.1-1.5 throw ratio and 4,500 ANSI lumens for clear, detailed images in compact spaces
- Golf Mode for Realistic Simulation: Designed for immersive play, Golf Mode supports major golf simulators for lifelike play on world-class virtual courses
- Large Screen Projection: Projects screen sizes from 80" to 150" with a throw distance of 6.7 ft - 12.5 ft; displays a 100" image from 8.3 ft
- Easy Setup & Image Adjustment: Features 1.3x optical zoom, 0.8x-2.0x digital zoom, H/V keystone, 360-degree projection, portrait mode, and 4-corner adjustment
- Advanced LAN Control: Remotely schedule and manage the projector via Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic vController
- Instant Power On/Off: Enables quick startup and shutdown with optional settings for automatic power control
- Installation Options: This projector is ceiling mountable; compatible with ViewSonic mount PJ-WMK-007



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1200
RESOLUTION



Product Description


Get bright, long-lasting performance without the hassle thanks to the ViewSonic® LS630W laser projector. Perfect for businesses and schools, this lamp-free WXGA projector delivers vibrant, clear images for up to 30,000 hours - that's years of use without a lamp replacement! With 4,500 ANSI lumens of brightness, your presentations and lessons will shine even in well-lit rooms. Flexible installation options, including compatibility with existing mounts and 360° projection, make upgrading a breeze. Plus, centralized LAN control simplifies management for IT teams. The LS630W offers a low total cost of ownership and hassle-free operation for a smart investment.

Specifications

UPC	766907031270
Light Source	DLP Laser
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	4,500 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	0.77-9.98m (100"@2.56m)
Throw Ratio	1.18-1.54
Keystone	Vertical ($\pm 30^\circ$) / Horizontal ($\pm 30^\circ$)
Lens	1.3x optical zoom
Light Source (watt)	Laser
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:10
Frequency Horizontal	15K-102KHz
Frequency Vertical	24-120Hz
PC Resolution (max)	1920 x 1200
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1200
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	175W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Kensington Lock Slot	1

Net (lbs)	6.8
Gross (lbs)	10.1
Net (kg)	3.1
Gross (kg)	4.6
Packaging (in.)	15.7 x 11.0 x 6.1
Physical (in.)	11.3 x 8.5 x 5.0
Packaging (mm)	400.0 x 280.0 x 155.0
Physical (mm)	286.0 x 216.0 x 129.0
Regulations	cTUVus
Package Contents	LS630W, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907031270



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com